

FEATURES & BENEFITS

- Designed to meet the requirements of PAS 23 and PAS 24
- Licensed by Secured by Design
- 10 Year Guarantee
- Available as 35mm and 45mm Backsets, with 16mm and 20mm face bars
- Non-handed lock mechanism with reversible sash bolt to minimise stock requirements
- Snib facility as standard on all locks
- Central brass deadbolt throws 22mm to prevent unauthorised entry
- Accepts standard 92mm unsprung handles and euro profile cylinders (operates with all BS and DIN specification cylinders and most other types of cylinder)
- Split spindle for lever/pad applications – choice of length available
- Bi-directional throw of locking features – enhanced anti-jemmy feature
- Twin high security forged brass hooks for anti-separation resistance-10mm (maximum) engagement into keeps.
- Hooks deadlocked in the fully thrown position
- Patented adjustable steel keeps giving $\pm 2.0\text{mm}$ for composite, timber and uPVC doors (non-adjustable composite and timber keeps also available)
- Easy-fit packer system for alternative profiles (PVCu application only)
- Optional shoot bolt engagement for additional security
- Single and French door (slave lock unit) application

LOCKING MECHANISM



KEEPS (COMPOSITE/TIMBER)



SHOOT BOLT (OPTIONAL)

